














Dengan hormat,





Kami PT. Endlessafe Sinergi Safetindo merupakan distributor resmi untuk produk-produk dibawah ini.





Bersama ini kami berikan penawaran harga fireman Suits dengan rincian sebagai berikut:

No	Picture	Product Name	Specifications	Certificate / Standard	Unit Price (Rp.)	Discount	Price after discount (Rp.)
Fire Safety Cabinet (Lemari Safety Pemadam)							
1		Lemari APD / Safety Cabinet Plat Besi Besar 2 pintu Size: T 180 x P 120 x L 40 cm Brand: ENDLESSAFE Model: ES-FSC-BS	1. Size: T 180 x P 125 x L 40 cm 2. Material : Mild Steel Plate (Plat besi) tebal 1,2mm 3. Finishing warna : coating powder cat merah 4. Dilengkapi 2 buah Pintu Kaca, 2 buah kunci, 2 buah handle, 4 buah roda double ball bearing Size: diameter 4 inch disertai fungsi rem yang di las ke rangka besi bawah 5. Terdapat Tiang gantungan untuk baju pemadam, rompi safety, dll 6. Terdapat 3 buah sekat 7. Terdapat 1 buah Palu pemecah kaca dengan rantai di sisi samping 8. Bonus 3 buah gantungan baju tebal		9.500.000	15%	8.075.000
2		Lemari APD / Safety Cabinet Aluminium Besar 2 pintu Size: T 180 x P 120 x L 40 cm Brand: ENDLESSAFE Model: ES-FSC-ALS	1. Size: T 180 x P 125 x L 40 cm 2. Rangka Aluminium 3. Sisi samping (kanan dan kiri), belakang, bawah, atas dan ambalan plat aluminium composite panel. 4. Dilengkapi dengan 4 buah roda double ball bearing Size: diameter 3 inchi disertai fungsi rem yang di las ke rangka besi bawah. 5. Dua buah pintu kaca dilengkapi kunci dan dimasing-masing pintu. 6. Terdapat tiang gantungan untuk pakaian pemadam, rompi safety, dll. 7. Bonus 3 buah gantungan baju tebal.		7.500.000	15%	6.375.000
3		Box APD / Safety Cabinet Plat Besi Kecil 2 pintu Size: T 100 x P 120 x L 40 cm Brand: ENDLESSAFE Model: ES-FSC-BSP	- Size: T 95 x P 125 x L 40 cm - Material : Mild Steel Plate (Plat besi) - Finishing warna : coating powder cat merah - 2 buah Pintu Kaca dilengkapi kunci - Tiang gantungan untuk baju pemadam, rompi safety, dll - 1 buah Palu pemecah kaca dengan rantai di sisi samping - Bonus 3 buah gantungan baju		6.000.000	15%	5.100.000
4		Box APD / Safety Cabinet Plat Besi Kecil 1 Pintu Size: T 100 x P 60 x L 40 cm Brand: ENDLESSAFE Model: ES-FSC-BSPS	- Size: T 95 x P 60 x L 40 cm - Material : Mild Steel Plate (Plat besi) - Finishing warna : coating powder cat merah - 1 buah Pintu Kaca dilengkapi kunci		3.500.000	15%	2.975.000
5		Fire Trolley / Trolley APAR Size: 100 x 90 x 60 cm Brand: ENDLESSAFE Model: ES-FTR	- Size: 100 x 90 x 60 cm - Material : Mild Steel Plate (Plat besi) - Finishing warna : coating powder cat merah - 2 buah Pintu Kaca di depan dan 1 pintu di atas - 4 buah roda double ball bearing Size: diameter 3 inch disertai fungsi rem yang di las ke rangka besi bawah		8.000.000	15%	6.800.000
Fireman Suits / Baju Anti Panas							
1		Fireman Suit (Jacket and Trouser) Brand: JJXF Model: ZFMH-JX D(DRD)	1) Outer fabric: Nomex IIIA 6oz (93% Nomex, 5% Kevlar, 2% P140, 205g/m2 ripstop) 2) Moisture Barrier : Aramid nonwoven + PTFE 108 g / m ² 3) Lining: 80% Nomex / 20% Kevlar thermal felt (75 g/m2) quilted to 50% Nomex / 50% Lenzing FR 4) Anti-Wicking: R45 Nomex + Chlorophene Rubber Coating (450 g/m2) 5) Elbow & knees protection fabric: Kevlar with black flame retardant PU coating 360 g/m2 6) Accessories Material: 3M scotchlite reflective stripe, metal zipper, flame retardant velcros, aramid thread 7) DRD (Drag Rescue Device) 8) Colors: Khaki, Red Orange and Navy Blue 9) Sizes: S, M, L, XL, XXL	CE / EN469 (Standard Eropa) Fire test report (from BTGG UK) Sertifikat Laporan Hasil Uji Lab Damkar	9.950.000	15%	8.457.500
2		Fireman Suit (Jacket and Trouser) Brand: ENDLESSAFE Model: ES-FM-ST-4L	1. Structure : 4 Layers 2. Outlayer : Oil resistant flame retardant cotton satin 3. Thermal barrier layer : 250g thermal insulation cotton 4. Lining layer : camlet 5. Flame Retardant Property : Damaged length<100mm,after flame times<2S 6. Fabric strength: tearing strength>40N, breaking strength>600N . 7. Detachable type 8. Weight: 3.2kg 9. Color: Orange 10. Size: S, M, L, XL, XXL	Uji lab Balai Besar Tekstil (Kementrian Perindustrian) ASTM D6413/D6413M-15 Sertifikat Laporan Hasil Uji Lab Damkar	3.600.000	15%	3.060.000
Fireman Aluminium Suit / Baju Aluminium Anti Api							
1		Aluminium foil heat insulation suit Brand: JJXF Model: RGF-F1	Structure: 3 Layers Outer layer: Kevlar + aluminum coated Thermal layer: aramid retardant insulatoin mat 170g/m2 Comfortable layer: lining natural cotton. Composition: Hood, Jacket, SCBA backpack, pants, gloves, insulated shoes. Temperature tolerance: 260°C TPP value: 25.0cal/cm2 Heat resistant: 1000 degree celsius radiation Flame retardant Property: damaged length 5mm, burn off time: 2S Weight: 4.2kg Size Option: S, M, L, XL, XXL	CE / EN1486 (Standard Eropa) C/W Fire test report	12.500.000	15%	10.625.000






2		<p>Aluminium foil heat insulation suit</p> <p>Brand: ENDLESSAFE Model: ES-FM-AFIS</p>	<p>Structure: 3 Layers Outer layer: Fiber Glass + aluminum coated Thermal layer: aramid retardant insulation mat Comfortable layer: lining natural fiber fabric. Composition: Hood, Jacket, SCBA backpack, pants, gloves, insulated shoes. Maximum Heat resistant: 550 degree celsius radiation Flame Retardant Property: damaged length 5mm Visor material: PES + silicon oxide/silve coating, 3mm thickness Inside Helmet: HDPE Weight: 5.7kg</p> <p>Size Option: S, M, L, XL, XXL</p>	Uji Lab Damkar / Fire Test Report	6.900.000	15%	5.865.000
3		<p>Aluminium foil heat insulation suit 500 Degree</p> <p>Brand: FIREFIGHTER Model : FF-AHRS-500C</p>	<p>Outer Shell: Aluminium foil composite with flame retardant fabric Thermal barrier: Aramid Felt Comfortable Lining: Aramid / Fire Retardant cotton woven fabric Maximum Heat Resistant <= 500 degree celcius Peeling Strength > 12N/5CM Breaking Strength > 650N Color: Silver Compositon: Hood, Jacket, SCBA backpack, pants, gloves, insulated shoes. Heat resistant: 500 degree celsius radiation Size: ALL SIZE</p>		4.950.000	15%	4.207.500
4		<p>Aluminium foil heat insulation suit for shio</p> <p>Brand: JIANGBO Model : DTXF-93-1</p>	<p>Model: DTXF-93-1 Type: For Ship Material: Acrylic fiber and aluminum foil without any asbestos Weight:7kg Heat Radiation ResancE: Under the heat radiation with 10kw/m 2 the increase of temperature: on inner-surface not over than 25°C after irradiate 30 seconds. Hydraulic preeure(static): ≥40000Pa Compositon: Coat;Helmet;Hood;Pant;Shooe;Boots Covering</p>	CCS / SOLAS	4.450.000	15%	3.782.500
5		<p>Aluminium foil heat insulation JACKET 1000C</p> <p>Brand: ANBOLY Model : ABL-F032</p>	<p>Material description: The new aramid 1313 woven fabric is used, and the aluminum plating process is adopted. It has the characteristics of no delamination, good firmness and softness. It is 3-5 times the service life of traditional aluminum foil materials; it can reflect 95% of the heat, Anti-radiant heat 1000 °C. It has the characteristics of good radiation resistance and thermal insulation performance. Uses: It is used in electrolytic aluminum, glass, casting, metallurgy and other industries to prevent aluminum water, steel flowers, molten iron splashing and high temperature radiation. Length: 120cm</p>		2.700.000	15%	2.295.000
6		<p>Aluminium foil heat insulation APPRON 1000C</p> <p>Brand: ANBOLY Model : ABL-V022</p>	<p>Material description: The new aramid 1313 woven fabric is used, and the aluminum plating process is adopted. It has the characteristics of no delamination, good firmness and softness. It is 3-5 times the service life of traditional aluminum foil aprons; it can reflect 95% of the heat, Anti-radiant heat 1000 °C. It has the characteristics of good radiation resistance and thermal insulation performance. Uses: It is used in electrolytic aluminum, glass, casting, metallurgy and other industries to prevent aluminum water, steel flowers, molten iron splashing and high temperature radiation. Length: 96cm</p>		900.000	15%	765.000

Fireman Gloves




1		<p>Fireman Gloves</p> <p>Brand: JJXF Model: JJXF-ST-2</p>	<p>1). Structure 4 layers Outer layer: aramid fire retardant fiber Waterproof layer: TPU low permeability Milky white waterproof bag Heat insulation layer: Aramid mats Inner layer: cotton 2) TPP ≥ 25.1cal/cm2 3) Wear-resisting propert: palm is over 2500N and back is over 2500N 4) Cutting force: palm ≥ 4 (15.0N) ≥ 4.0N (15.0N), back; 5) Tear force: palm ≥ 100N (178.2N); 7)reflective tape: 360° reflective logo and width not less than 50mm belt.</p> <p>Color Option: Khaki, Navy Blue and Orange Size: S, M, L, XL, XXL</p>	CE / EN659 (Standard Eropa) C/W Fire Test Report Sertifikat Laporan Hasil Uji Lab Damkar	580.000	15%	493.000
2		<p>Fireman Gloves</p> <p>Brand: ANBEN-FIRE Model: 2-A (Khaki) Model: 2-B (Orange) Model: 2-C (Navy Blue)</p>	<p>1). Structure 4 layers Outer layer: Nomex blended fabric Moisture barrier: Nomex substrate with PTFE membrane Thermal lining: Aramid Comfortable layer: Viscose woven blended fabric 2) TPP ≥ 35 cal/cm2 3) Length: 27cm 4) Weight: 350gr 5) Color Option: Khaki, Orange and Navy Blue</p> <p>Size: ALL SIZE</p>	CE / EN659 (Standard Eropa) C/W Fire Test Report	580.000	15%	493.000
3		<p>Fireman Gloves</p> <p>Brand: HYGLOVES Model: 7883</p>	<p>- Treated premium split cowhide outer shell, palm reinforced - Polyurethane moisture barrier branded - Heat and flame resistant Kovenex lining - 3D design, roll-over seamless fingertips, super mobility - Two-ply Kevlar wristlet with leather pull-tab cuff</p>	NFPA 1971-2018	2.350.000	15%	1.997.500
4		<p>Leather Forest Fire Gloves</p> <p>Brand: ANBEN-FIRE Model: AB-ST-01</p>	<p>1) Materials: cowhide leather 2) Features: Waterproof and steamproof 3) Wearable Heat resistant 4) Anti-static Lining, knitted threaded mouth (comportable fit) 5) Color: Yellow 6) Length: 27cm 7) Weight: 300gr</p> <p>Size: All Size</p>	CE / EN659 (Standard Eropa) C/W Fire Test Report Sertifikat Laporan Hasil Uji Lab Damkar	650.000	15%	552.500

5		<p>Long Leather Fireman Gloves</p> <p>Brand: ANBEN-FIRE Model: AB-ST-02</p>	<p>1) Materials: cowhide leather 2 layers 2) Moisture barrier: TPU low permeability 3) Anti-static lining, knitted threaded mouth (comfortable fit) 4) Waterproof and steamproof wearable heat resistant 5) Features: Waterproof and steamproof 6) Wearable Heat resistant 7) There are hooks easy carrying 8) 5cm reflective strip, eye cathing 9) Color: black 10) length: 40cm 11) 350gr</p> <p>Size: All Size</p>	CE / EN659 (Standard Eropa) C/W Fire Test Report	700.000	15%	595.000
6		<p>Fireman Gloves</p> <p>Brand: ENDESSAFE Model: ES-FM-GV-4L</p>	<p>Structure: 4 layers (wearable, anti-slip) Outer shell: high strength fabric with flame retardant,wear-resisting, anti- puncture Waterproof layer: waterproof and moisture permeable fabrics. Heat insulatoin layer: aramid mats Inner layer: cotton Function: Anti-slip, anti-puncture termal resistant and flame retardant properites. Color: Orange</p> <p>All Size</p>	Uji lab Batali Besar Tekstil (Kementrian Perindustrian) ASTM D6413/D6413M- 15	250.000	15%	212.500
7		<p>Aluminium Heat Resistant Glove 500 °C</p> <p>Brand: ANBOLY Model: ABL-S521</p>	<p>Material: The palm is made of 1414 para-aramid dense woven fabric, the back of the hand is made of aluminium foil high temperatur resistant fabric, and the inside is aramid insulation felt and comfort layer. Product performance: wear-resistant, anti-radiant, excellent thermal insulation, temperatur resistance 500 °C Product use: use in steel manufacturing, metallurgy and other furnance operation to wear. Lenght: 36cm size: ALL SIZE</p>	CE EN407	680.000	15%	578.000
8		<p>Aluminium Heat Resistant Glove 1000 °C</p> <p>Brand: ANBOLY Model: ABL-S515</p>	<p>1. It has good high temperature resistance and anti-cutting performance; 2. The palm is reinforced to increase the wear resistance of the gloves and prolong the use time; 3. High temperature resistance of 1000 degrees (short-term contact: 3-5 seconds) 4. The outer layer is made of Made of KEVLAR® and carbon fiber blended fabrics, the inner layer is made of carbon fiber insulation felt and multi-layer flame-retardant fire-resistant felt; 5. Low thermal conductivity, not easy to ignite; 6. Wear-resistant, high strength; 7. Adopt five-finger design, Flexible activities and easy to use; 8. length: 38cm 9. Size: ALL SIZE</p>	CE EN407	1.750.000	15%	1.487.500




Fireman Hood, Mask & Safety Goggles

1		<p>Fireman Hood</p> <p>Brand: JJXF Model: MRT-L-JJ01</p>	<p>1) Best heat insulation performance provides the best protection. Comfortable, More Durability and Strength. 2) Structure: 2 layers 3) Material: 50%nomex 50%Vicose FR 4) Thermal stability, shrinkage: 4.1% 5) Pilling resistance: level 4 6) Seam Strength: 916.7N 7) Weight: 153.6g</p> <p>Color Option: White and Black All size</p>	CE / EN13911 (Standard Eropa) c/w Fire Test Report	580.000	15%	493.000
2		<p>Full Face Mask double respirator c/w filter</p> <p>Brand: NA&UM Model: FM-252B</p>	<p>Features: Full Face Design Cold Breathing Valve Adjustable Strap</p> <p>*#Package Content 1 x Full Face Gas Mask 2 x Cartridge 2 x Cotton Filter 2 x Filter Cap</p>		950.000	15%	807.500
3		<p>Full Face Gas Mask Single Respirator c/w Carbon Active Filter Tank</p> <p>Brand: YIGU Model: A300</p>	<p>Breathing valve resistance: 59Pa Lens Transmittance: > 90% Leakage rate of close-fitting mask: < 0,02% Total Vision: 80% Binocular Vision: 60% Lower view: 36% Interface specification: threaded interface RD40 Material: - Screen: Polycarbonate - Mouth and Nose mask: food grade liquid silicone - Headband: Flame retardant and fireproof fiber - Face Mask: medical grade liquid silicone - Frame: ABS</p>		1.050.000	15%	892.500
4		<p>Fire Escape Mask</p>	<p>This respirator is intended for applications in governmental institution, hotels, office building, forests, air ports, department stores, banks ships, post offices, powder industry, telecommunications, subways, recreation centers, refineries and chemical industry, etc, as an essential breathing-protective device for personal safety in fire accidents.</p> <p>Penetration coefficient of oil mist: > 98% Wearing quality: 650g Suction temperature: not more than 65 °C Oil fog through factor: no more than 5%</p>		350.000	15%	297.500
5		<p>Safety Goggles Full</p> <p>Brand: ENDESSAFE Model: ES-SGF</p>	<p>Lens Color: Clear (bening) Frame Color: Clean or Red Size: Adult, unisex Frame: Full view frame Material: PVC frame, PC lens Weight Net : 110 gram Packing: Carton box</p> <p>FEATURES: 1. Anti-scratch 2. Anti-fog 3. Anti-ultraviolet (UV400) 4. Anti-splash</p>		100.000	15%	85.000




Fireman Boot

1		Fireman Boot Brand: JJXF Model: RJX25A	1) Material: Polythene Rubber, steel toe, steel midsole 2) Oil resistant property: upper9.5% side 9.8%, bottom5.8% 3) Anti drop performance : static pressure 21mm ; impact 25.5mm ; 4) .Puncture resistance: 1825N 5) Electrical insulation: Withstand voltage:≥5000V; 6) Thermal insulation performance: 4°C ; 7) Anti slip: >15o ; 8) Weight: 2.4kg Size: 38-46	CE / EN15090 (Standard Eropa) c/w Fire Test Report Sertifikat Laporan Hasil Uji Lab Damkar	1.250.000	15%	1.062.500
2		Fireman Boot Brand: FireFighter	Specification: Upper: Polythene Rubber Midsole: steel Toecap: steel Features: flame retardant, heat insulation, high voltage resistant, oil resistant , anti slip, anti acid and alkali		800.000	15%	680.000
3		Fireman boot Brand: Harvik Model: 9687L	Flame retardant rubber outsole. Fuel oil resistant sole suitable for inimical environment. Slip resistant vulcanized rubber outsole. Non-corrosive stainless steel. Epoxy coated toe caps. High visibility with black and yellow contrast. Waterproof. Reinforced rubber. Meets EN ISO 25345 impact and compression tests.	CE / EN 15090 MED AS/NZS 4821	2.300.000	15%	1.955.000


Fireman Helmet










1		Fireman Helmet Brand: JJXF Model:RMK-LH	1). Shell: injection molding, thermoplastic PA66 2). Faceshield: light colored, transparent, high temperature resistant polyethersulfone; 3). Shawl: Aramid+aluminium coated; navy blue cotton oil/flame retardant twill, double layer structure 4). Temperature resistance: 260 Celcius Degree 5). Maximum impact force: 3327.6N 6). Weight: 1.16kgs Color Option: Red and Yellow	CE / EN433 (Standard Eropa) c/w Fire Test Report Sertifikat Laporan Hasil Uji Lab Damkar	2.400.000	15%	2.040.000
2		Fireman Helmet Brand: ANBEN FIRE Model: AB-B/A	· Outer Shell Material: Polyetherimide (PEI) · Face Shield Material: Polycarbonate · Mesh-type Buffer Layer · Adjustable Helmet Size · Adjustable Chin strap · Shawl: Aramid+Aluminium Foil · Reflective Tape: Yellow · Six-point Support System · Color: Red	-CE / EN433 (Standard Eropa) c/w Fire Test Report	1.500.000	15%	1.275.000
3		Rescue Helmet Brand: ANBEN FIRE Model: F2	Material: Polyetherimide (PEI) Color: Red Hat strap material: Aramid Cushioning material: EVA Adjustable leather headband 52-64cm Features: - Shock abosorption (top / lateral) - Penetration resistance - Lateral deformation resistace - Protection againts high speed particles Include in package: Helmet + Torch Holder + Safety goggles	CE / EN433 (Standard Eropa) c/w Fire Test Report	1.820.000	15%	1.547.000






Safety Helmet & Safety Vest

1		Safety Helmet MSA (Lokal)	Helm Proyek / Safety Helmet MSA Lokal sudah SNI Sudah Termasuk Inner FasTrack suspension Belum Termasuk Tali dagu Pilihan warna : Putih, Kuning, Hijau, Biru, Merah, Orange		110.000	15%	93.500
2		Tali Dagu/Chinstrap/Tali Dagu Helm Proyek MSA Lokal	Dilengkapi dengan tali dagu yang sangat elastis dan untuk merenggang serta kuat. Dudukan dagu / Mangkuk dagu yang terbuat dari bahan pilihan menimbulkan sensasi nyaman bagi para penggunakanya.		25.000	15%	21.250
3		Hi-Visibility Safety Vest with reflective stripes and Pockets Brand: ENDESSAFE Model: ES-SV-HVW1	Safety vest / rompi safety di lengkapi dengan reflektf strip 2 kantong ukuran besar dengan tutup 1 kantong ukuran sedang 1 tempat kartu pengenalan zipper (seleting) All Size		90.000	15%	76.500






Anti-Bee Suit & Chemical Suit



1		Anti-Bee Suit Brand: JJXF Model: FPS60	Anti-bee suit is a protective device worn by firefighters to prevent wasps from biting the body when removing a wasp nest. With anti-cutting, anti-acid, anti-alkali, anti-venom and other protective functions, novel style, reasonable structure. It's made of flame retardant polyvinyl chloride. The utility model is composed of a cowl, jumpsuit, rubber boots, puncture-proof gloves, etc. Face mask is made of hard PC material. The air holes and breathing holes can effectively prevent wasps from spraying poison needles. 1. Strength of the fabric: Tensile strength: warp & weft ≥450N/5cm Tear strength: ≥32N 2. Chemical resistant boots: Sole electrical insulation: ≥5000V Puncture resistance of sole: ≥1500N 3. Weight: ≤4 kg; Packing size: 560 × 525 × 410 mm Size: L & XL		5.500.000	15%	4.675.000
---	--	---	--	--	------------------	------------	------------------

2		Bee Keeping Suit Brand: ENDESSAFE Model:	Material: cotton Features: 1. Easy to Carry: The clothes are easy to carry and bite-proof, keeping your inner clothes clean. 2. Premium Material: This honey clothes set is made of natural cotton, and it comes with removable scarf and headscarf. 3. Comfortable to Wear: Tailored with elastic waistband and elastic ankles. The clothes are comfortable to wear. 4. Unisex Design: Unisex design for men and women. With removable veil hood; easy to clean and easy to store. 5. Stylish Design: The softer clothes come with elastic band for better protection. Include in package: 1 x Protective Clothing for Beekeeping 1 x Beekeeping Gloves		700.000	15%	595.000
3		Semi-Enclosed Light chemical protective clothing Brand: ANBEN Model: RFH-01	Material:Flame Resistant PVC Color:Red Thickness of material:0.45±0.05mm. Weight:5kg Tensile Strength:warp and weft direction ≥450N/5cm. Tear Strength:≥32N. Anti-acid and alkali penetration performance:10mm liquid column is impermeable for 1h. Gasoline resistance:120# gasoline soaks for 30s without cracks and stickiness. Flame retardant performance:continuous burning times2s, flame retardant times10s, damage length≤10cm, no drop Electrical insulation performance of shoe sole:≥5000v. Puncture resistance of the sole:≥780N. Waterproof performance of boots:Soak in water for 2h, no water seepage. Adhesive strength of stickers:≥0.78kn/m Water leakage resistance:5 nozzles of 3L/min will not leak after 15 minutes of washing Package: suit, boot and gloves	CE EN13034	3.750.000	15%	3.187.500
Immersion Suit / Marine Survival Suit							
1		Immersion Suit / Marine Survival Suit Brand: FANGZHAN Model: FZBW-II	waterproof dry suit intended to protect the wearer from hypothermia if immersed in cold water or otherwise exposed after abandoning a vessel, especially in the open ocean. Using waterproof neoprenen of reddish orange color With life jacket light and whistle Comprising jacket and trousers with reflective bands Color: Red Size: L and XL		4.800.000	15%	4.080.000
Emergency Escape Breathing Device (EEBD) & Self Contained Breathing Apparatus (SCBA)							
1		Emergency Escape Breathing Device (EEBD) Brand: FANGZHAN Model: TH/15-1	Spesifikasi: Working Pressure of the Cylinder:21MPa (210 Bar) Cylinder Volume:3 L Air Deposit: 625 L Using time: > 15 Menit (25 L/Min) Weight: < 7,5kg Kelengkapan: - HEAD COVER - STEEL CYLINDER 3 LITER - PRESSURE GAUGE-METER INDICATOR for EEBD - RUBBER HOSE - BAG CASE/ SATCHEL ASSEMBLY	MED/3.41 EN1146 ISO 23269-1 CSS / SOLAS 74	3.800.000	15%	3.230.000
2		Breathing Apparatus (SCBA) - Steel Cylinder 6 Liter Brand: KAEN Model: G-F-6.0	Volume : 6 Litre Working Pressure : 30 Mpa (300 Bar) Period : 50-60 min Cylinder Material : Steel Include in package: full face mask, Backing, Gas cylinder, valve with pressure gauge, medium pressure pipe, assembly, High-pressure connector, Positive pressure air control device, pressure relief valve assembly, box.	CE EN 14593-1	8.400.000	15%	7.140.000
3		Breathing Apparatus (SCBA) - Steel Cylinder 6 Liter Brand: ENDESSAFE Model: RHZKF6/30	Volume : 6 Litre Working Pressure : 30 Mpa (300 Bar) Period : 50-60 min Cylinder Material : Steel Include in package: full face mask, Backing, Gas cylinder, valve with pressure gauge, medium pressure pipe, assembly, High-pressure connector, Positive pressure air control device, pressure relief valve assembly, box.	Garansi 1 tahun Jaminan ketersediaan sparepart selama 5 tahun	8.400.000	15%	7.140.000
4		Breathing Apparatus (SCBA) - Steel Cylinder 6 Liter Brand: FANGZHAN Model: RHZK6	Volume : 6 Litre Working Pressure : 30 Mpa (300 Bar) Period : 50-60 min Cylinder Material : Steel Include in package: full face mask, Backing, Gas cylinder, valve, medium pressure pipe, assembly, High-pressure connector, Positive pressure air control device, pressure relief valve assembly, box.	CCS SOLAS MED Approval, EC certificate	9.000.000	15%	7.650.000
5		Breathing Apparatus (SCBA) - Steel Cylinder 6 Liter Brand: JIANGBO Model: RHZK 6/30	Volume : 6 Litre Working Pressure : 30 Mpa (300 Bar) Period : 50-60 min Cylinder Material : Steel Include in package: full face mask, Backing, Gas cylinder, valve, medium pressure pipe, assembly, High-pressure connector, Positive pressure air control device, pressure relief valve assembly, box.	CCS SOLAS MED Approval	8.700.000	15%	7.395.000
6		Breathing Apparatus (SCBA) - Composite Cylinder 6,8 Liter Brand: KAEN Model: RHZKF6.8/30	Volume : 6.8 Litre Working Pressure : 30 Mpa (300 Bar) Period : 60-65min Cylinder Material : Composite Include in package: full face mask, Backing, Gas cylinder, valve with pressure gauge, medium pressure pipe, assembly, High-pressure connector, Positive pressure air control device, pressure relief valve assembly, box.	CE EN 14593-1	9.900.000	15%	8.415.000









7		<p>Breathing Apparatus (SCBA) - Composite Cylinder 6,8 Liter</p> <p>Brand: ENDLESSAFE Model: RHZKF6.8/30</p>	<p>Volume : 6.8 Litre Working Pressure : 30 Mpa (300 Bar) Period : 60-65min Cylinder Material : Composite c/w Pressure Gauge in the valve cylinder</p> <p>Include in package: full face mask, Backing, Gas cylinder, valve with pressure gauge, medium pressure pipe, assembly, High-pressure connector, Positive pressure air control device, pressure relief valve assembly, box.</p>	<p>Garansi 1 tahun Jaminan ketersediaan sparepart selama 5 tahun</p>	9.900.000	15%	8.415.000
8		<p>Breathing Apparatus (SCBA) - Composite Cylinder 6,8 Liter</p> <p>Brand: JIANGBO Model: RHZKF 6.8/30</p>	<p>Volume : 6.8 Litre Working Pressure : 30 Mpa (300 Bar) Period : 60-65min Cylinder Material : Composite</p> <p>Include in package: full face mask, Backing, Gas cylinder, valve with pressure gauge, medium pressure pipe, assembly, High-pressure connector, Positive pressure air control device, pressure relief valve assembly, box.</p>	<p>MED Approval, EC certificate</p>	11.475.000	15%	9.753.750
9		<p>Breathing Apparatus (SCBA) - Coumposite Cylinder 6,8 Liter</p> <p>Brand: HONEYWELL Model: T8000</p>	<p>Backplate : Flame Retardant Polyamid-Fibre Glass Harness : Nomex + Kevlar Clynder Strap : Nomex Demand Valve : PBT/PC dilapasi Rubber Skirt and Inner Mask Material : EPDM Visor : PC class 3 dengan Anti Gores</p> <p>Cyinder Material: Composite with aluminium liner Capacity: 6.8 Liter Working Pressure: 300 BAR</p>	<p>CE / EN137 (Standard Eropa)</p>	32.000.000	15%	27.200.000
10		<p>Breathing Apparatus (SCBA) - Coumposite Cylinder 6,8 Liter</p> <p>Brand: MSA Model: AirXpress 2 Fire</p>	<p>BD Backplate: word-renowned design AutoMaxx-AS demand valve Gauge cap Pneumatic systems based on the alpha platform Padded harness, with reflective logo on the shoulder strap Integrated transponder for storage control</p> <p>Capacity: 6.8 Liter Working Pressure: 250 BAR Cyinder Material: Coumposite</p>	<p>CE / EN137 (Standard Eropa)</p>	39.000.000	15%	33.150.000
11		<p>Electric Air Supply Long Tube Respirators</p> <p>Brand: ANBEN FIRE Model: YGDFA-20</p>	<p>Sheel Material: Stainless Steel Working Power: 220VAC/50HZ Operating Voltage: 12V DC Working Current: 6.0A Mask Air Volume: > 30L/Minutes Fan Air Volume: 190L/Minutes Rated Power: 140W Noise Intensity: <76.1DB(A) Hose Material: Medical Grade</p>		14.500.000	15%	12.325.000



Flash Light

1		<p>Mini Flashlight LED USB Rechargeable</p> <p>Brand: TaffLED</p>	<p>XML-T6 6250 Lumens 10W - P15 Tipe LED T6 Lumens 6250 Lumens Tipe Baterai 18650 Rechargeable Lithium Battery Dimensi 12 (length) x 2.7 (main diameter) x 2.4 (tail diameter)</p> <p>Include in package: 1 x flashlight 1 x Baterai 18650 (rechargeable) 1 x USB cable</p>		150.000	15%	127.500
2		<p>Senter Besar 40W Rechargeable</p> <p>Brand: AOKI Mode: AK-8100L</p>	<p>DESKRIPSI: 1. Diameter lensa 11,1 cm 2. Menggunakan baterai cas ulang, kapasitas besar Lhitium 4V 5000mAh(18650 X 3pcs) 3. Menggunakan baterai awet, dapat dicas ulang lebih dari 500 kali 4. Dilengkapi LED yg tahan lama, sangat terang dan hemat energi 5. Menggunakan 40W LED HALOGEN</p> <p>isi dalam box : - 1 unit senter jumbo - 1 pc tali (strap) - 1 pc adaptor</p>		375.000	15%	318.750
3		<p>Explosion proof torch Rechargeable</p> <p>Brand: JUUPAI Model: SDLL-I</p>	<p>Product size 25*131mm (diameter/length) product weight: 138g Rated power: 3W Rated voltage: 3.7V 2600mAh power supply Lighting time: 3~6h Product material: Aluminum alloy Ambient temperature: -20~+40°C Explosion-proof grade: Ex ic IIC T4 GC Average service life: 100000h</p> <p>Include in package: flashlight + USB Type C cable + Charger + Bracket</p>	<p>CNEX</p>	750.000	15%	637.500
4		<p>Portable explosion proof flashlight</p> <p>Brand: JIAN BO Model: JH-6Z</p>	<p>1. The product's shell material painted with fine lacquer layer is made of aluminum alloy. 2. Lamp shell doesn't have through-hole, the lamp's switch on-off uses the structure of dry spring of alarm circuits and strong magnetic switch to ensure the explosion-proof character. 3. The lamp has safety lock clamping screw nail ensuring the closure of the lamp in inflammable and explosives locations. The lamp cover can only be opened in safe place by person in charge of using special spanner when the electricity is off. 4. Battery: 6pcs Battery Type D / R25S (non rechargeable) 5. Duration: ≥3h 6. Light bulb: 7.2V 0.5A 7. Explosion-proof class: IP65</p>	<p>CCS</p>	950.000	15%	807.500
5		<p>Portable explosion proof flashlight IP66</p> <p>Brand: FANGZHAN Model: FZ-6</p>	<p>1. The product's shell material painted with fine lacquer layer is made of ZDL-102 aluminum alloy. 2. Lamp shell doesn't have through-hole, the lamp's switch on-off uses the structure of dry spring of alarm circuits and strong magnetic switch to ensure the explosion-proof character. 3. The lamp has safety lock clamping screw nail ensuring the closure of the lamp in inflammable and explosives locations. The lamp cover can only be opened in safe place by person in charge of using special spanner when the electricity is off. 4. Battery: 5pcs Battery Type D / R25S (non rechargeable) 5. Duration: 3h 6. LED Lamp 7. Explosion-proof class: IP66</p>	<p>CCS</p>	1.100.000	15%	935.000








6		<p>Explosion proof flash light rechargeable</p> <p>Brand: JIANGBO Model: JH-6Z-II</p>	<p>Model: Portable type Rated Voltage:3.6V Main Material: ZLD102 Power Source:2x3.6v LITHIUM BATTERY Burning Period:More than 3hours Degrees of Protection:IP65</p>	CSS	2.700.000	15%	2.295.000
7		<p>Headlamp LED Rechargeable</p> <p>Brand: TaffLED Model: KX-1804</p>	<p>LED Model of LED: 1*XPE +1*COB Luminious Flux Lumens: 180lm (COB), 100lm (XPE) Battery Type 18650 (rechargeable) Length 8.5cm x 3.8cm x 4cm Water resist - splashproof</p> <p>isi dalam box : - 1 unit headlamp - 1 pc tali (strap) - 1 pc battery 18650 (rechargeable) - 1 pc USB cable</p>		150.000	15%	127.500

Stretcher & First Aid Kit






1		<p>Tandu Lipat 2 Aluminium</p> <p>Brand: GEA Model: YDC 1 A9</p>	<p>Dimensi Produk: 2210 x 525 x 150mm Dimensi Produk terlipat: 1100 x 180 x 225mm Berat Bersih: 6 Kg Berat Maksimal: 159 Kg Terdapat shield belt Terdapat tas tandu lipat Pegangan tandu dari bahan karet</p>		1.750.000	15%	1.487.500
2		<p>Tandu Lipat 4 Aluminium</p> <p>Brand: GEA Model: YDC 1 A10</p>	<p>- Size: terbuka (tandu dibuka) : 213cm (p) x 56cm (L) x 15cm (T) - Size: tertutup (tandu ditutup) : 104cm (p) x 19cm (L) x 12cm (T) - Berat tandu : 5 kg - ada tas warna orange - Bahan Aluminium TEBAL, TDK BISA BERKARAT - Mampu menampung beban sampai dengan 159 Kg - Terdapat 2 buah sabuk pengaman sehingga pasien lebih aman dan tidak jatuh</p>		1.995.000	15%	1.695.750
3		<p>Long Spine Board Stretcher</p> <p>Brand: GEA Model: YDC 7 B2</p>	<p>Made of PE material with no discharge contaminator and firmness to wear Allowed x ray Compatible with head immobile at the same time Mainly used for hospitals,sports,ambulance and outdoors carrying patients and wounded person</p>		2.200.000	15%	1.870.000
4		<p>Spider Strap for Long Spine Board Stretcher</p> <p>Brand: UNICARE Model: RC-SS1</p>	<p>1. This product made of Polypropylene. 2. It can fixed on spine board / long spinal board</p>		540.000	15%	459.000
5		<p>Head Immobilizer</p> <p>Brand: UNICARE Model: RC-G1</p>	<p>1. This product made of foam sponge. 2. Unique head chin strap is designed to conform to patient's forehead. 3. Large ear holes for monitoring the patient's ear canal. 4. Minimal interference with X-ray,MRI or CT scan procedures. 5. Waterproof vinyl dipped foam makes it easy to clean. 6. Compatible with all flat backboard, Compatible with Spine board and cervical collars.</p>		1.650.000	15%	1.402.500
6		<p>Basket Stretcher</p> <p>Brand: UNICARE Model: RC-R2</p>	<p>1. This product made of ABS, wear-resisting, corrosion proof. 2. It's separable, can save the store space. 3. It's for the rescue in mountain area, air, sea and so on, credibility and flexible. 4. With one set of the rope, can be for plane lifting. 5. With feet fixing device, safety belts and mattress.</p> <p>Product Size(L*W*H)(Open): 216*61*19cm Product Size(L*W*H)(Folded): 130*61*26cm Self weight: 20kg Max Load :160kg</p>		12.500.000	15%	10.625.000
7		<p>Stair Evacuation Chair Stretcher</p> <p>Brand: UNICARE Model: RC-D1</p>	<p>1.This product made of high quality aluminum. 2.For transferring the patients in small space. 3.With foldable lifting handles. 4.With four castors. 5.Can be folded and store in the ambulance.</p> <p>Product Size(L*W*H)(Open): 52*48*91cm Product Size(L*W*H)(Folded) :91*52*19cm Weight: 11kg Max Load :160kg</p>		5.850.000	15%	4.972.500
8		<p>Collar Neck / Cervical Collar /penyangga leher</p> <p>Brand: GEA Model: CC-01</p>	<p>Bahan dari busa dan Plastik sehingga sangat nyaman dan berfungsi untuk mengurangi dan terapi kerusakan jaringan lunak pada leher , Osteoarthritis dan cedera whiplash. Dengan design berventilasi sehingga mampu untuk mensirkulasi udara sehingga membuat kulit tetap bisa bernafas Disesuaikan dengan dagu sehingga memberikan kenyamanan saat digunakan Mengurangi pergerakan selama proses pemulihan Mencegah pergerakan tulang servical sehingga mempercepat proses penyembuhan Mengurangi rasa sakit Dapat disesuaikan ukuran kecil besarnya leher pada perekat</p>		300.000	15%	255.000











8		<p>Soft collar Neck / Cervical Collar /penyangga leher</p> <p>Brand: LP Model: 906</p>	<p>LP Cervical Collar is made of 17mm medium density foam, covered by cotton stockinette, with a contoured cut for the chin. A hook and loop closure in back for easy adjustment.</p> <p>Features :</p> <ul style="list-style-type: none"> - Flexion and extension of the cervical spine is largely prevented by the neck collar. Other movements are limited only from painful extreme positions. - LP cervical collar can also be used at night for postural correction. - Provides therapeutic support following neck injury. 		400.000	15%	340.000
9		<p>P3K / First Aid Kit/ Tipe C</p>	<p>Tas Emergency Selempang, sudah termasuk Isi P3K Tipe C. Sesuai peraturan kemeterian untuk pegawai maksimal 100 orang.</p>		990.000	15%	841.500





Fire Blanket

1		<p>Fire Blanket (PVC Box Case) Size: 1,2 x 1,2 m</p> <p>Brand: ANBEN FIRE</p>	<ul style="list-style-type: none"> •Lebar / Panjang : 1.2 meter / 1.2 meter •Tebal : 0.4 mm •Material : Fiberglass •Temperatur : 550°C •Standard: CE / EN-1869:2019 •Packing: Hard PVC Box 	CE / EN 1869:2019	250.000	15%	212.500
2		<p>Fire Blanket (PVC Box Case) Size: 1,2 x 1,8 m</p> <p>Box</p> <p>Brand: ANBEN FIRE</p>	<ul style="list-style-type: none"> •Lebar / Panjang : 1.2 meter / 1.8 meter •Tebal : 0.4 mm •Material : Fiberglass •Temperatur : 550°C •Standard: CE / EN-1869:2019 •Packing: Hard PVC Box 	CE / EN 1869:2020	300.000	15%	255.000
3		<p>Fire Blanket (PVC Box Case) Size: 1,8 x 1,8 m</p> <p>Box</p> <p>Brand: ANBEN FIRE</p>	<ul style="list-style-type: none"> •Lebar / Panjang : 1.8 meter / 1.8 meter •Tebal : 0.4 mm •Material : Fiberglass •Temperatur : 550°C •Standard: CE / EN-1869:2019 •Packing: Hard PVC Box 	CE / EN 1869:2021	350.000	15%	297.500
4		<p>Fire Blanket (Bag Case) Size: 1 x 1 m</p>	<ul style="list-style-type: none"> •Lebar / Panjang : 1 meter / 1 meter •Tebal : 0.4 mm •Material : Fiberglass •Temperatur : 550°C •Standard: CE / EN-1869:2019 •Packing: Bag 		175.000	15%	148.750
5		<p>Fire Blanket (Bag Case) Size: 1,2 x 1,2 m</p>	<ul style="list-style-type: none"> •Lebar / Panjang : 1.2 meter / 1.2 meter •Tebal : 0.4 mm •Material : Fiberglass •Temperatur : 550°C •Standard: CE / EN-1869:2019 •Packing: Bag 		200.000	15%	170.000
6		<p>Fire Blanket (Bag Case) Size: 1,2 x 1,8 m</p>	<ul style="list-style-type: none"> •Lebar / Panjang : 1.2 meter / 1.8 meter •Tebal : 0.4 mm •Material : Fiberglass •Temperatur : 550°C •Standard: CE / EN-1869:2019 		225.000	15%	191.250
7		<p>Fire Blanket (Bag Case) Size: 1,8 x 1,8 m</p>	<ul style="list-style-type: none"> •Lebar / Panjang : 1.8 meter / 1.8 meter •Tebal : 0.4 mm •Material : Fiberglass •Temperatur : 550°C •Standard: CE / EN-1869:2019 		250.000	15%	212.500

Axe (Kampak)

1		<p>Fire Axe / Kapak Damkar 25cm Model: ES-FM-AXE-25i</p>	<p>2 Mata Panjang 25cm Gagang Karet Import</p>		225.000	15%	191.250
2		<p>Kapak Damkar / Fire Axe 60cm Wood Handle</p> <p>Brand: ENDLESAFE Model: ES-FM-AXE-60i</p>	<p>Type: Double Head Panjang 60cm Gagang Kayu Import</p>		370.000	15%	314.500
3		<p>Kapak Damkar / Fire Axe 90cm Wood Handle</p> <p>Brand: ENDLESAFE Model: ES-FM-AXE-90i</p>	<p>Type: Double Head Panjang 90cm Gagang Kayu Import</p>		370.000	15%	314.500
4		<p>Kapak Damkar / Fire Axe 90cm Fiberglass Handle</p> <p>Brand: ENDLESAFE Model: ES-FM-AXE-90Fi</p>	<p>Type: Double Head Material: Drop forged high carbon steel. Heat treated. Surface of head: Red colour painted, blade with polished Handle: Wooden handle/ Fiberglass handle. Length: 90cm Import</p>		800.000	15%	680.000
5		<p>Kapak dua fungsi (kapak cangkul) / Pulaski axe with fiberglass handle</p> <p>Brand: ENDLESAFE Model: ES-FM-AXP-90Fi</p>	<p>Type: Pulaski Head Weight: 3.5lb Material: Drop forged high carbon steel. Heat treated. Surface of head: Painted, blade polished Handle: Fiberglass handle. Application: Forestry Fire fighting Import</p>		800.000	15%	680.000

6		Hooligan Tool / Halligan Tool with Standard Claw for Forcible entry, Rescue and Fire fighting Brand: ENDESSAFE Model: ES-FM-HGI	The Hooligan Tool / Halligan Tool is one of the world's most popular forcible entry tools. This tool is designed to pry, pound, puncture, twist, and cut open or remove all types of barriers between emergency service personnel and the ability to save a life. The head and claw are forged from high alloy steel, heat treated for maximum strength, then fitted to a stress proof bar. The bar has machine grooved non-slip grips. Import		5.550.000	15%	4.717.500
7		Fire fighting hook Pike pole Brand: ENDESSAFE Model: ES-FM-PP-Fbi	The pike pole's original use in the fire service was to pull down walls and neighboring buildings to stop a fire's spread. Hook Material: Carbon steel Handle Material: Fiberglass Surface: Painted Application: Fire fighting and rescue, Logging Import		1.500.000	15%	1.275.000
Peralatan emergency & rescue lainnya							
1		Megaphone TOA with Sirene include battery	Output : Rated 15W Power Source : 9V DC R14P (SUM-2) or "C" Batteries AA 6 pcs Audible Range : Talk : Approx. 400m Sirene : Approx. 500m Sirene Mode : Push to talk Outer Horn Diameter : 210 mm Length : 310 mm Weight : 980 g		1.350.000	15%	1.147.500
2		35kV High Voltage Fiberglass Insulating Rescue Hook	The Rescue Hook to assist in the removal of an injured worker from a hazardous area (near electrical gear, vaults, confined spaces etc). Material: Fiberglass Length: 2M 35KV Weight: 2.1kg double section		7.500.000	15%	6.375.000
3		RESCUE TRIPOD Brand: KAEN Model: JSJ-S	Working load (winch) : 200-500kg Blocking force (winch) : 22KN Fully expanded : 222cm Complete Contraction : 141cm Max lifting weight : 1600N Material : High strength aluminum alloy Steel cable(winch) : 30M Gear ratio (winch) : 5:1 Blocking force : 500kg Packing Size : 176x28x25cm Weight : ≤31kg	CE EN 360:2002 CE EN 363:2008	15.000.000	15%	12.750.000
4		Body Harness Brand: MSA Model: V-FORM	The MSA V-FORM™ safety harnesses, with lightweight and durable components, offer the user complete comfort. The harness straps are available in the catchy combination of MSA green and gray. Harness V-Form, Back D-Ring, front loops, shoulder loops, bayonet buckles, MED/LG, EN< /li> Double load indicator warns you when the harness has been involved in a fall Strap ends do not fray and lasts longer Includes a strap under the pelvis for more comfort< /li> A Velcro® cover protects harness tag 140kg load capacity V-Form waist belt attaches to harness for work positioning		2.940.000	15%	2.499.000
5		Lanyard double hook Brand: MSA Model: 10212148	Style: Double large hooks color: White Hook material: galvanized steel Standard lace length: 1.2m Standard: GB6095-2009 Minimum breaking strength of webbing: 24KN Minimum breaking strength of hook: 22KN Material: Polyester		2.340.000	15%	1.989.000
6		Axial fan 12 inch + 5 meter duct hose Brand: CKE	Spesifikasi Axial Fan / Portable Ventilator : Size 12" Power 310W Voltage 220V Air Flow 2120CFM Speed 2800RPM Pressure 345Pa Spesifikasi Duct Hose: Diameter 12" Length 5M Material Fireproof PVC		4.900.000	15%	4.165.000
Eye Wash							
1		Emergency Eye Wash Bottle Brand: UNICARE Model: 6670	emergency flushing bottle is suitable for local skin and eye irrigating. It can deal with the acid and alkali liquid on the skin with emergency skin solution. The capacity of each bottle is 500ML. The material of the container is made of non-toxic materials of polyethylene. Specifications: Materials: non-toxic materials of polyethylene Color: Green Water pressure :0.2-0.4kg/cm2 Speed:2-3liter/min. Capacity: 2 bottles x 500ml		1.050.000	15%	892.500
2		Emergency Eye Wash Portable 30L (8 gallons) Brand: UNICARE Model: RYBX003	Eyewash Material: Environmental PE Material of catchment tank: SS304 Colour: Green and Yellow Volume: 8 gallons (30L) Features: No installation, no restrictions on the use of the environment Use of water source temperature: 8-40 degrees Celsius Time of use: >15MIN Intake size: 80mm Spacing of eyewash nozzles: 100mm Size Length/Width/Height:550*250*360mm Production Standard: ANSIZ358.1-2014		3.500.000	15%	2.975.000

3		<p>Emergency Eye Wash Wall Mounted</p> <p>Brand: UNICARE Model: RYBG001</p>	<p>Material: Stainless Steel 304 / SS304 Function: Eye and face rinse Nominal pressure: 1.0 Mpa Work pressure: 0.2-0.4 Mpa Test pressure: 2.0 Mpa Use ambient temperature: 0-40°C Washing Water Flow: 11.4 L/MIN Eyewash flow:>1.5L/MIN Inlet size: 1/2 inch internal thread Drainage outlet size: 1-1/4 inch Production Standard: ANSI Z358.1-2014</p>	1.750.000	15%	1.487.500
3		<p>Emergency Eye Wash Wall Mounted Elbow</p> <p>Brand: UNICARE Model: RYBG002</p>	<p>Material: Stainless Steel 304 / SS304 Function: Eye and face rinse Nominal pressure: 1.0 Mpa Work pressure: 0.2-0.4 Mpa Test pressure: 2.0 Mpa Use ambient temperature: 0-40°C Washing Water Flow: 11.4 L/MIN Eyewash flow:>1.5L/MIN Inlet size: 1/2 inch internal thread Drainage outlet size: 1-1/4 inch Production Standard: ANSI Z358.1-2014</p>	2.200.000	15%	1.870.000
4		<p>Emergency Eye Wash Standing</p> <p>Brand: UNICARE Model: RYLS002</p>	<p>Material: Stainless Steel 304 / SS304 Function: Eye and face rinse Nominal pressure: 1.0 Mpa Work pressure: 0.2-0.4 Mpa Test pressure: 2.0 Mpa Use ambient temperature: 0-40°C Eye/Face Washing Water Flow: >11.4 L/MIN Eyewash flow: 1.5L/MIN Influent height: 850 mm Drainage height: 101mm Inlet size: 1/2 inch internal thread Drainage outlet size: 1 -1/4 inch internal thread Foot pedal: add foot pedal, wash eyes open and close more convenient Production Standard: ANSI Z358.1-2014</p>	3.540.000	15%	3.009.000
5		<p>Emergency Eye Wash and Shower Station</p> <p>Brand: UNICARE Model: RYFH002</p>	<p>Material: Stainless Steel 304 / SS304 Function: Spray + Eyewash Top Spray: Rotary Ball Valve: Two-piece Ball Valve Dust-proof: integrated fixed type Eye wash basin: 300 mm straight edge design Running water diameter: 42 mm Nominal pressure: 1.0 Mpa Work pressure: 0.2 - 0.4 Mpa Test pressure: 2.0 Mpa Use ambient temperature: 0-40°C Spray water flow: >75.7L/MIN eye/Face Washing Water Flow:>11.4L/min Eyewash flow: >1.5 L/MIN Eyewash nozzle: equipped with dual flow control valve Influent height: 1440 mm Drainage height: 101mm Drainage outlet size: 1-1/4 inch internal thread Foot pedal: stepping on stable and easy to operate Production Standard: ANSI Z358.1-2014</p>	5.950.000	15%	5.057.500

Keterangan:

1. Harga belum termasuk PPN 11%
2. Harga bisa berubah sewaktu waktu, mohon untuk konfirmasi stock dan harga sebelum order

Demikian penawaran harga yang dapat kami sampaikan, silahkan menghubungi kami bila Bapak/Ibu membutuhkan klarifikasi lebih lanjut. Atas perhatian dan kerjasamanya kami ucapkan terima kasih.